

Safety Data Sheets (SDS)

#### Section 1 – Identification

1(a) Product Identifier used on Label: Stainless Steel Scrap

1(b) Other means of identification: Stainless Steel Scrap Products (All Grades), SDS ID: FE-0104 1(c) Recommended use of the chemical and restrictions on use: Scrap metal use. None Known

1(d) Name, address, and telephone number:

OmniSource Corporation Phone: (260) 664-4789 (Safety Department)

7575 West Jefferson Blvd Fort Wayne, Indiana 46804

1(e) Emergency Phone Number: (800) 424-9300 (CCN# 221258) CHEMTREC

### Section 2 – Hazard(s) Identification

**2(a)** Classification of the chemical: Stainless Steel Scrap is considered an article under Reach regulation (REACH REGULATION (EC) No 1907/2006) and is not subject to classification under CLP regulation (REGULATION (EC) No 1272/2008). However, Stainless Steel Scrap is not exempt as an article under OSHA's Hazard Communication Standard (29 CFR 1910.1200) due to its downstream use, thus this product is considered a mixture and a hazardous material. Therefore, the categories of Health Hazards as defined in "GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELING OF CHEMICALS (GHS), Third revised edition ST/SG/AC.10/30/Rev. 3" United Nations, New York and Geneva, 2009 have been evaluated. Refer to Section 3, 8 and 11 for additional information.

2(b) Signal word, hazard statement(s), symbols and precautionary statement(s):

Hazard Symbol	Hazard Classification	Signal Word	Hazard Statement(s)	
	Carcinogenicity - 1B Reproductive Toxicity - 2 Single Target Organ Toxicity (STOT) Repeat Exposure - 1 Respiratory Sensitization - 1B	DANGER	May cause cancer.  Suspected of damaging fertility or the unborn child.  Causes damage to lungs and central nervous system through prolonged or repeated inhalation exposure.	
NA NA	Skin Sensitization - 1 Single Target Organ Toxicity (STOT) Repeat Exposure - 3  Eye Irritation - 2B	DANGER	May cause allergy or asthma symptoms or breathing difficulties if inhaled.  May cause an allergic skin reaction.  May cause respiratory irritation.  Causes eye irritation.	

#### **Precautionary Statement(s):**

Treatment (s)		
Prevention	Response	Storage/Disposal
Do not breathe dusts or fumes.  In case of inadequate ventilation, wear respiratory protection.  Wear protective gloves / protective clothing / eye protection / face protection.  Contaminated work clothing must not be allowed out of the workplace.  Wash thoroughly after handling.  Obtain special instructions before use.  Do not handle until all safety precautions have been read and	Response  If exposed, concerned or feel unwell: Get medical advice/attention.  If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If you are experiencing respiratory symptoms: Call a poison center or doctor/physician.  If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.	Dispose of contents in accordance with federal, state and local regulations.  Store locked up.
understood. Use only outdoors or in a well-ventilated area.	If on skin: Wash with plenty of water. If irritation or rash occurs: Get medical advice/attention. Take off and wash	
In case of inadequate ventilation, wear respiratory protection.	contaminated clothing before reuse.	

2(c) Hazards not otherwise classified: None Known

2(d) Unknown acute toxicity statement (mixture): None Known

### Section 3 – Composition/Information on Ingredients

3(a-c) Chemical name, common name (synonyms), CAS number and other identifiers, and concentration: **Chemical Name** % weight **CAS Number EC Number** 7439-89-6 231-096-4 >45 Iron Nickel 7440-02-0 231-111-4 < 36 7440-47-3 231-157-5 <27 Chromium Tungsten 7440-33-7 231-143-9 < 20 7440-48-4 231-158-0 <12 Cobalt



Safety Data Sheet (SDS)

Revision: 06/13/2018

C 42 2	C	/T C 42	. T.,	( 4 <u>-</u> 1)
Section 4 —	( amnacitian	/Intarmatian ar	1 Ingredients	i continued i
Section 5 -	Composition	/Information or	i ingiculcing	(COIIIIIIUCU)

3(a-c) Chemical name, common name (synonyms), CAS number and other identifiers, and concentration (continued):

S(a-c) Chemical name, common name (synonyms), CAS number and other fuentiners, and concentration (continued).					
Chemical Name CAS Num		EC Number	% weight		
Molybdenum	7439-98-7	231-107-2	<10		
Copper	7440-50-8	231-159-6	<5		
Aluminum	7429-90-5	231-072-3	<5		
Manganese	7439-96-5	231-105-1	<5		
Vanadium	7440-62-2	231-171-1	<3		
Silicon	7440-21-3	231-130-8	<3		
Carbon	7440-44-0	231-153-3	<3		

EC - European Community

CAS - Chemical Abstract Service

This product contains small amounts of various elements in addition to those listed. These small quantities are frequently referred to as "trace" or "residual" elements that generally originate in the raw materials used. Steel products may contain the following trace or residual elements at below 0.1%: calcium, arsenic, lead, tin, niobium, boron, and zirconium.

#### Section 4 – First-aid Measures

- 4(a) Description of necessary measures: If exposed, concerned or feel unwell: Get medical advice/attention.
- Inhalation: Stainless Steel Scrap as sold/shipped is not a likely form of exposure. If inhaled: Remove person to fresh air and keep comfortable for breathing. If you feel unwell or are experiencing respiratory symptoms: Call a poison center or doctor/physician.
- Eye Contact: Stainless Steel Scrap as sold/shipped is not a likely form of exposure. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- Skin Contact: If on skin: Wash with plenty of water. If irritation or rash occurs: Get medical advice/attention. Take off and wash contaminated clothing before reuse.
- Ingestion: Stainless Steel Scrap as sold/shipped is not a likely form of exposure. If swallowed: Call a poison center or doctor/physician if you feel unwell. Rinse mouth.
- 4(b) Most important symptoms/effects, acute and delayed (chronic):
  - Inhalation: Stainless Steel Scrap as sold/shipped is not likely to present an acute or chronic health effect.
  - Eye: Stainless Steel Scrap as sold/shipped is not likely to present an acute or chronic health effect.
  - Skin: Stainless Steel Scrap as sold/shipped is not likely to present an acute or chronic health effect.
- Ingestion: Stainless Steel Scrap as sold/shipped is not likely to present an acute or chronic health effect.

However, during further processing (welding, grinding, burning, etc.) individual components may illicit an acute or chronic health effect. Refer to Section 11-Toxicological Information.

4(c) Immediate Medical Attention and Special Treatment: None Known

### **Section 5 – Fire-fighting Measures**

- **5(a) Suitable (and unsuitable) Extinguishing Media:** Not Applicable for **Stainless Steel Scrap** as sold/shipped. Use extinguishers appropriate for surrounding materials.
- 5(b) Specific Hazards arising from the chemical: Not Applicable for Stainless Steel Scrap as sold/shipped. When burned, toxic smoke, fume and vapor may be emitted.
- **5(c) Special protective equipment and precautions for fire-fighters:** Self-contained NIOSH approved respiratory protection and full protective clothing should be worn when fumes and/or smoke from fire are present. Heat and flames cause emittance of acrid smoke and fumes. Do not release runoff from fire control methods to sewers or waterways. Firefighters should wear full face-piece self-contained breathing apparatus and chemical protective clothing with thermal protection. Direct water stream will scatter and spread flames and, therefore, should not be used.

#### **Section 6 - Accidental Release Measures**

- **6(a) Personal Precautions, Protective Equipment and Emergency Procedures:** Not Applicable for **Stainless Steel Scrap** as sold/shipped. For spills involving finely divided particles, clean-up personnel should be protected against contact with eyes and skin. If material is in a dry state, avoid inhalation of dust.
- **6(b) Methods and materials for containment and clean up:** Not Applicable for **Stainless Steel Scrap** as sold/shipped. Collect material in appropriate, labeled containers for recovery or disposal in accordance with federal, state, and local regulations. Follow applicable OSHA regulations (29 CFR 1910.120) and all other pertinent state and federal requirements.

### **Section 7 - Handling and Storage**

7(a) Precautions for safe handling: Not Applicable for Stainless Steel Scrap as sold/shipped, however further processing (welding, burning, grinding, etc.) with the potential for generating high concentrations of airborne particulates should be evaluated and controlled as necessary. Wear protective gloves / protective clothing / eye protection / face protection. Contaminated work clothing must not be allowed out of the workplace. Wash thoroughly after handling. In case of inadequate ventilation, wear respiratory protection. Obtain special instructions (continued)...



Safety Data Sheet (SDS)

Revision: 06/13/2018

### Section 7 - Handling and Storage (continued)

7(a) Precautions for safe handling (continued): ... before use. Do not handle until all safety precautions have been read and understood. Practice good housekeeping. Do not breathe breathing metal fumes and/or dust. Do not eat, drink or smoke when using this product. Cut resistant gloves and sleeves should be worn when working with steel products.

7(b) Conditions for safe storage, including any incompatibilities: Store away from acids and incompatible materials.

### **Section 8 - Exposure Controls / Personal Protection**

**8(a) Occupational Exposure Limits (OELs): Stainless Steel Scrap** as sold/shipped in its physical form does not present an inhalation, ingestion or contact hazard, nor would any of the following exposure data apply. However, operations such as burning, welding (high temperature), sawing, brazing, machining, grinding, etc may produce fumes and/or particulates. The following exposure limits are offered as reference for an experienced industrial hygienist to review:

Ingredients	OSHA PEL <sup>1</sup>	ACGIH TLV <sup>2</sup>	NIOSH REL <sup>3</sup>	IDLH <sup>4</sup>
Iron	10 mg/m³ (as iron oxide fume)	5.0 mg/m³ (as iron oxide dust and fume)	5.0 mg/m³ (as iron oxide dust and fume)	2,500 mg Fe/m <sup>3</sup>
Nickel	1.0 mg/m³ (as Ni metal & insoluble compounds)	1.5 mg/m³ (as inhalable fraction⁵ Ni metal) 0.2 mg/m³ (as inhalable fraction Ni inorganic only insoluble and soluble compounds)	0.015 mg/m³ (as Ni metal & insoluble and soluble compounds)	10 mg/m³ (as Ni)
Chromium	0.5 mg/m³ (as Cr II & III, inorganic compounds)	0.5 mg/m³ (as Cr III, inorganic compounds)	0.5 mg/m³ (as Cr II & III, inorganic compounds)	250 mg/m³ (as Cr II & metal)
	1.0 mg/m³ (as Cr, metal)	0.5 mg/m³ (as Cr, metal)	0.5 mg/m³ (as Cr, metal)	25 mg/m³ (as Cr III)
	0.005 mg/m³ (as Cr VI, inorganic compounds & certain water insoluble)	0.05 mg/m³ (as Cr VI, inorganic compounds)	0.001 mg/m³ (as Cr VI, inorganic compounds &	15 mg/m³ (as Cr VI)
	"AL" 0.0025 mg/m³ (as Cr VI, inorganic compounds & certain water insoluble)	0.01 mg/m³ (as Cr VI, inorganic compounds & certain water insoluble)	certain water insoluble)	
Tungsten	NE	$5.0 \text{ mg/m}^3$	$5.0 \text{ mg/m}^3$	NE
		10 mg/m³	"STEL" 10 mg/m	
Cobalt	0.1 mg/m <sup>3</sup>	$0.02 \text{ mg/m}^3$	$0.5 \text{ mg/m}^3$	20 mg/m <sup>3</sup> (as Co)
Molybdenum	15 mg/m³ (as total dust, PNOR <sup>6</sup> ) 5.0 mg/m³ (as respirable fraction, PNOR)	10 mg/m³ (as Mo insoluble compounds, inhalable fraction)	NE	NE
		3.0 mg/m³ (as Mo insoluble compounds, respirable fraction <sup>7</sup> )		
		0.5 mg/m³ (as Mo soluble compounds, respirable fraction)		
Copper	0.1 mg/m³ (as fume, Cu)	0.1 mg/m³ (as fume)	1.0 mg/m³ (as dusts & mists)	100 mg Cu/m <sup>3</sup>
	1.0 mg/m³ (as dusts & mists, Cu)	1.0 mg/m³ (as dusts & mists, Cu)		
Aluminum	15 mg/m³ (as total dust, PNOR)	10 mg/m³ (as metal dust)	10 mg/m³ (as total dust)	NE
	5.0 mg/m³ (as respirable fraction, PNOR)	5.0 mg/m³ (as welding fume)	5.0 mg/m³ (as respirable dust)	
Manganese	(C) 5.0 mg/m³ (as Fume & Mn compounds)	0.2 mg/m³	(C) 5.0 mg/m <sup>3</sup> 1.0 mg/m <sup>3</sup> (as fume) (STEL) 3.0 mg/m <sup>3</sup>	500 mg Mn/m <sup>3</sup>
Vanadium	"C" 0.5 mg/m³(respirable dust, V <sub>2</sub> O <sub>5</sub> )	0.05 mg/m³ (as inhalable fraction <sup>7</sup> )	"C" 0.05 mg/m <sup>3</sup> (15 min)	35 mg/m³ (as V)
Silicon	15 mg/m³ (total dust, PNOR)	10 mg/m³	10 mg/m³ (as total dust)	NE
	5.0 mg/m³ (as respirable fraction, PNOR)	<u> </u>	5.0 mg/m³ (as respirable dust)	
Carbon	15 mg/m³ (as total dust, PNOR)	10 mg/m³ (as inhalable fraction, PNOS)	NE	NE
	5.0 mg/m³ (as respirable fraction, PNOR)	3.0 mg/m³ (as respirable fraction, PNOS8)		

#### NE - None Established

- 1. OSHA Permissible Exposure Limits (PELs) are 8-hour TWA (time-weighted average) concentrations unless otherwise noted. A (C) designation denotes a ceiling limit, which should not be exceeded during any part of the working exposure unless otherwise noted. A Peak is defined as the acceptable maximum peak for a maximum duration above the ceiling concentration for an eight-hour shift. A skin notation refers to the potential significant contribution to the overall exposure by the cutaneous route, either by contact with vapors or, of probable greater significance, by direct skin contact with the substance. A Short Term Exposure Limit (STEL) is defined as a 15-minute exposure, which should not be exceeded at any time during a workday. An Action level (AL) is used by OSHA and NIOSH to express a health or physical hazard. They indicate the level of a harmful or toxic substance/activity, which requires medical surveillance, increased industrial hygiene monitoring, or biological monitoring. Action Levels are generally set at one half of the PEL but the actual level may vary from standard to standard. The intent is to identify a level at which the vast majority of randomly sampled exposures will be below the PEL.
- 2. Threshold Limit Values (TLV) established by the American Conference of Governmental Industrial Hygienists (ACGIH) are 8-hour TWA concentrations unless otherwise noted. A Short Term Exposure Limit (STEL) is defined as the maximum concentration to which workers can be exposed for a short period of time (15 minutes) for only four times throughout the day with at least one hour between exposures. A "skin" notation refers to the potential significant contribution to the overall exposure by the cutaneous route, either by contact with vapors or, of probable greater significance, by direct skin contact with the substance. ACGIH-TLVs are only recommended guidelines based upon consensus agreement of the membership of the ACGIH. As such, the ACGIH TLVs are for guideline use purposes and are not legal regulatory standards for compliance purposes. The TLVs are designed for use by individuals trained in the discipline of industrial hygiene relative to the evaluation of exposure to various chemical or biological substances and physical agents that may be found in the workplace.

Safety Data Sheet (SDS)

### Section 8 - Exposure Controls / Personal Protection (continued)

#### 8(a) Occupational Exposure Limits (OELs) (continued):

- 3. The National Institute for Occupational Safety and Health Recommended Exposure Limits (NIOSH-REL) Compendium of Policy and Statements. NIOSH, Cincinnati, OH (1992). NIOSH is the federal agency designated to conduct research relative to occupational safety and health. As is the case with ACGIH TLVs, NIOSH RELs are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes.
- 4. The "immediately dangerous to life or health air concentration values (IDLHs)" are used by NIOSH as part of the respirator selection criteria and were first developed in the mid-1970's by NIOSH. The Documentation for Immediately Dangerous to Life or Health Concentrations (IDLHs) is a compilation of the rationale and sources of information used by NIOSH during the original determination of 387 IDLHs and their subsequent review and revision in 1994.
- 5. Inhalable fraction. The concentration of inhalable particulate for the application of this TLV is to be determined from the fraction passing a size-selector with the characteristics defined in the ACGIH 2017 TLVs ® and BEIs ® (Biological Exposure Indices) Appendix D, paragraph A.
- 6. PNOR (Particulates Not Otherwise Regulated). All inert or nuisance dusts, whether mineral, inorganic, or organic, not listed specifically by substance name are covered by the PNOR limit which is the same as the inert or nuisance dust limit of 15 mg/m<sup>3</sup> for total dust and 5.0 mg/m<sup>3</sup> for the respirable fraction (containing less than 1% crystalline silica).
- 7. Respirable fraction The concentration of respirable dust for the application of this limit is to be determined from the fraction passing a size-selector with the characteristics defined in the ACGIH 2017 TLVs® and BEIs® Appendix D, paragraph C.
- 8. PNOS (Particulates Not Otherwise Specified). Particulates identified under the PNOS heading are "nuisance dusts" containing no asbestos and <1% crystalline silica

**8(b)** Appropriate Engineering Controls: Use controls as appropriate to minimize exposure to metal fumes and dusts during handling operations. Provide general or local exhaust ventilation systems to minimize airborne concentrations. Local exhaust is necessary for use in enclosed or confined spaces. Provide sufficient general/local exhaust ventilation in pattern/volume to control inhalation exposures below current exposure

#### 8(c) Individual Protection Measures:

• Respiratory Protection: Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, use only a NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. Concentration in air of the various contaminants determines the extent of respiratory protection needed. Half-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 10 times the exposure limit. Full-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 50 times the exposure limit. Protection by air-purifying negativepressure and powered air respirators is limited. Use a positive-pressure-demand, full-face, supplied air respirator or self-contained breathing apparatus (SCBA) for concentrations above 50 times the exposure limit. If exposure is above the IDLH (Immediately dangerous to life or health) for any of the constituents, or there is a possibility of an uncontrolled release or exposure levels are unknown, then use a positivedemand, full-face, supplied air respirator with escape bottle or SCBA.

Warning! Air-purifying respirators both negative-pressure, and powered-air do not protect workers in oxygen-deficient atmospheres.

- Eyes: Wear appropriate eye protection to prevent eye contact. For operations which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulates, use safety glasses to prevent eye contact. Contact lenses should not be worn where industrial exposures to this material are likely. Use safety glasses or goggles as required for welding, burning, sawing, brazing, grinding or machining operations.
- Skin: Wear appropriate personal protective clothing to prevent skin contact. Cut resistant gloves and sleeves should be worn when working with steel products. For operations which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulates, use protective clothing, and gloves to prevent skin contact. Protective gloves should be worn as required for welding, burning or handling operations. Contaminated work clothing must not be allowed out of the workplace.
- Other protective equipment: An eyewash fountain and deluge shower should be readily available in the work area.

#### **Section 9 - Physical and Chemical Properties**

9(a) Appearance (physical state, color, etc.): Depends upon scrap

composition, most often appears as a silvery-white metal

9(b) Odor: Odorless 9(c) Odor Threshold: NA

9(d) pH: NA

9(e) Melting Point/Freezing Point: 2800°F

9(f) Initial Boiling Point and Boiling Range: 5400°F

9(g) Flash Point: NA

9(h) Evaporation Rate: NA

9(i) Flammability (solid, gas): Non-flammable, non-combustible

NA - Not Applicable

ND - Not Determined for product as a whole

9(j) Upper/lower Flammability or Explosive Limits: NA

Revision: 06/13/2018

9(k) Vapor Pressure: ND

9(l) Vapor Density (Air = 1): NA

9(m) Relative Density: 8 SG

9(n) Solubility(ies): Water Insoluble

9(o) Partition Coefficient n-octanol/water: ND

9(p) Auto-ignition Temperature: NA 9(q) Decomposition Temperature: ND

9(r) Viscosity: NA

### **Section 10 - Stability and Reactivity**

10(a) Reactivity: Not Determined (ND) for product in a solid form. Do not use water on molten metal.

10(b) Chemical Stability: Steel products are stable under normal storage and handling conditions.

10(c) Possibility of hazardous reaction: None Known

10(d) Conditions to Avoid: Storage with strong acids or calcium hypochlorite.



Safety Data Sheet (SDS)

### Section 10 - Stability and Reactivity (continued)

10(e) Incompatible Materials: Will react with strong acids to form hydrogen. Iron oxide dusts in contact with calcium hypochlorite evolve oxygen and may cause an explosion.

**10(f) Hazardous Decomposition Products:** Thermal oxidative decomposition of steel products can produce fumes containing oxides of iron and manganese as well as other alloying elements.

### **Section 11 - Toxicological Information**

11 Information on toxicological effects: The following toxicity data has been determined for Stainless Steel Scrap when further processed using the information available for its components applied to the guidance on the preparation of an SDS under the GHS requirements of OSHA and the EU CPL:

Hazard Classification	Hazard Category Hazard		Signal Word	Hazard Statement	
	EU	OSHA	Symbols		
Eye Damage/Irritation (covers Categories 1, 2A & 2B)	NA*	2B °	NA	Warning	Causes eye irritation.
Skin/Dermal Sensitization (covers Category 1)	NA*	1 <sup>d</sup>		Warning	May cause an allergic skin reaction.
Respiratory Sensitization (covers Category 1A & 1B)	NA*	$1\mathrm{B}^{\mathrm{d}}$		Warning	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Carcinogenicity (covers Categories 1A, 1B and 2)	NA*	$1\mathrm{B}^\mathrm{g}$		Warning	May cause cancer.
<b>Toxic Reproduction</b> (covers Categories 1A, 1B and 2)	NA*	1 <sup>h</sup>		Danger	May damage fertility or the unborn child.
Specific Target Organ Toxicity (STOT) Following Single Exposure (covers Categories 1-3)	NA*	3 <sup>i</sup>		Warning	May cause respiratory irritation.
STOT following Repeated Exposures (covers Categories 1 and 2)	NA*	1 <sup>j</sup>		Danger	Causes damage to lungs and central nervous system through prolonged or repeated inhalation exposure.

<sup>\*</sup> Not Applicable - Semi-formed steel products are considered articles under Reach regulation (REACH REGULATION (EC) No 1907/2006) and are not subject to classification under CLP regulation (REGULATION (EC) No 1272/2008).

Toxicological data listed below are presented regardless to classification criteria. Individual hazard classification categories where the toxicological information has met or exceeded a classification criteria threshold are listed above.

- a. No LC<sub>50</sub> or LD<sub>50</sub> has been established for **Stainless Steel Scrap**. The following data has been determined for the components:
  - **Iron:** Rat LD<sub>50</sub> =98.6 g/kg (REACH)

Rat LD<sub>50</sub> =1060 mg/kg (IUCLID)

Rat  $LD_{50} = 984 \text{ mg/kg (IUCLID)}$ 

Rabbit LD<sub>50</sub> =890 mg/kg (IUCLID)

- Nickel: LD<sub>50</sub> >9000 mg/kg (Oral/Rat)
- Copper: Rat  $LD_{50} = 481 \text{ mg/kg}$  (REACH)

Rat  $LD_{50} > 2500$  mg/kg (REACH)

• Carbon: LD<sub>50</sub>= >10,000 mg/kg (Oral/ Rat)

- **Cobalt:** LD50 = 10 mg/L(rat)
  - $LD_{50} = 500 \text{ mg/kg (Oral/Rat)}$
- Silicon:  $L_{D50} = 3160 \text{ mg/kg (Oral/Rat)}$
- Aluminum: Rat LD<sub>50</sub> > 15.9 g/kg (REACH)
- Manganese: Rat LD<sub>50</sub> > 2000 mg/kg (REACH)

Rat  $LD_{50} > 9000 \text{ mg/kg}$  (NLM Toxnet)

Revision: 06/13/2018

- Vanadium Pentoxide: LD<sub>50</sub> = 145 mg/kg (Oral/Mouse)
- b. No Skin (Dermal) Irritation data available for **Stainless Steel Scrap** as a mixture. The following Skin (Dermal) Irritation information was found for the components:
  - Molybdenum: May cause skin irritation.
- c. No Eye Irritation data available for **Stainless Steel Scrap** as a mixture. The following Eye Irritation information was found for the components:
  - Iron and Molybdenum: Causes eye irritation.
  - Nickel: Slight eye irritation from particulate abrasion only.
- d. No Skin (Dermal) Sensitization data available for **Stainless Steel Scrap** as a mixture. The following Skin (Dermal) Sensitization information was found for the components:
  - Nickel: May cause allergic skin sensitization.
  - Cobalt: Skin Sensitizing In vitro mouse local lymph node. Guinea Pig Maximization test and patch test sensitizing.
- e. No Respiratory Sensitization data available for Stainless Steel Scrap as a mixture or its components.



Safety Data Sheet (SDS)

Revision: 06/13/2018

### Section 11 - Toxicological Information (continued)

#### 11 Information on toxicological effects (continued):

- f. No Germ Cell Mutagenicity data available for **Stainless Steel Scrap** as a mixture. The following Mutagenicity and Genotoxicity information was found for the components:
  - Nickel: EU RAR has found positive results in vitro and in vivo but insufficient data for classification.
  - Iron: IUCLID has found some positive and negative findings in vitro.
- g. Carcinogenicity: IARC, NTP, and OSHA do not list **Stainless Steel Scrap** as carcinogens. The following Carcinogenicity information was found for the components:
  - Nickel and certain nickel compounds Group 2B metallic nickel Group 1 nickel compounds ACGIH confirmed human carcinogen. Nickel –
    EURAR Insufficient evidence to conclude carcinogenic potential in animals or humans; suspect carcinogen classification Category 2 Suspected of causing cancer.
  - Chromium (as metal and trivalent chromium compounds) IARC Group 3 carcinogens, not classifiable as to their human carcinogenicity.
  - Welding Fumes IARC Group 2B carcinogen, a mixture that is possibly carcinogenic to humans.
  - Cobalt IARC Group 2B carcinogen possibly carcinogenic to humans. ACGIH TLV-A3.
  - Vanadium Pentoxide: IARC 2B, ACGIH Animal carcinogen A-4. 104 wk Rat inhalation carcinogenicity some evidence of lung neoplasms in males. 104 wk Mouse inhalation carcinogenicity clear evidence of carcinogenicity.
- h. No Toxic Reproduction data available for **Stainless Steel Scrap** as a mixture. The following Toxic Reproductive information was found for the components:
  - Nickel: Effects on fertility.
- i. No Specific Target Organ Toxicity (STOT) following a Single Exposure data available for **Stainless Steel Scrap** as a mixture. The following STOT following a Single Exposure data was found for the components:
  - Iron and Molybdenum: Irritating to Respiratory tract.
  - Aluminum: Repeated exposure associated with Asthma, fibrosis in lungs and encephalopathy in humans.
  - Vanadium Pentoxide: Kidney, lung, and thorax cardiac rate increased.
- j. No Specific Target Organ Toxicity (STOT) following Repeated Exposure data was available for **Stainless Steel Scrap** as a mixture. The following STOT following Repeated Exposure data was found for the components:
  - Nickel: Rat 4 wk inhalation LOEL 4 mg/m³ Lung and Lymph node histopathology. Rat 2 yr inhalation LOEL 0.1 mg/m³ Pigment in kidney, effects
    on hematopoiesis spleen and bone marrow and adrenal tumor. Rat 13 Week Inhalation LOAEC 1.0 mg/m³ Lung weights, and Alveolar
    histopathology.
  - Copper: Target organs affected Skin, eyes liver, kidneys and respiratory tract.
  - Manganese: Inhalation of metal fumes Degenerative changes in human Brain; Behavioral: Changes in motor activity and muscle weakness (Whitlock et al., 1966).
  - Aluminum: Reviews have found chronic exposure to aluminum flake has been reported to cause pneumoconiosis in workers. Repeat oral exposure
    to aluminum results in decrements in neurobehavioral function and development.
  - Vanadium Pentoxide: Rat 90 da feeding LOEL 3 mg/kg based on erythropenia, anemia in all groups. Rat 16 da inhalation LOEC = 2 mg/m³ based on survival and inflammation in Lung (NTP Study). Rat 90 da inhalation NOAEC 1 mg/m³ based on lung effects (NTP and REACH).

The above toxicity information was determined from available scientific sources to illustrate the prevailing posture of the scientific community. The scientific resources includes: The American Conference of Governmental Industrial Hygienist (ACGIH) Documentation of the Threshold Limit Values (TLVs) and Biological Exposure indices (BEIs) with Other Worldwide Occupational Exposure Values 2017, The International Agency for Research on Cancer (IARC), The National Toxicology Program (NTP) updated documentation, the World Health Organization (WHO) and other available resources, the International Uniform Chemical Information Database (IUCLID), European Union Risk Assessment Report (EU-RAR), Concise International Chemical Assessment Documents (CICAD), European Union Scientific Committee for Occupational Exposure Limits (EU-SCOEL), Agency for Toxic Substances and Disease Registry (ATSDR), Hazardous Substance Data Bank (HSDB), and International Programme on Chemical Safety (IPCS).

The following health hazard information is provided regardless to classification criteria and is based on the individual component(s) and potential resultant components from further processing:

#### Acute Effects:

- Inhalation: Excessive exposure to high concentrations of metal dust may cause irritation to the eyes, skin and mucous membranes of the upper respiratory tract. Excessive inhalation of fumes of freshly formed metal oxide particles sized below 1.5 micrometer and usually between 0.02-0.05 micrometers from many metals can produce an acute reaction known as "metal fume fever". Symptoms consist of chills and fever (very similar to and easily confused with flu symptoms), metallic taste in the mouth, dryness and irritation of the throat followed by weakness and muscle pain. The symptoms come on in a few hours after excessive exposures and usually last from 12 to 48 hours. Long-term effects from metal fume fever have not been noted.
- Eye: Excessive exposure to high concentrations of metal dust may cause irritation to the eyes.
- Skin: Skin contact with metal dusts may cause irritation or sensitization, possibly leading to dermatitis. Skin contact with metallic fumes and dusts may cause physical abrasion.
- Ingestion: Ingestion of harmful amounts of this product as distributed is unlikely due to its solid insoluble form. Ingestion of metal dust may cause nausea or vomiting.

#### **Acute Effects by component:**

- Iron and iron oxides: Iron is harmful if swallowed, causes skin irritation, and causes eye irritation. Contact with iron oxide has been reported to cause skin irritation and serious eye damage. Particles of iron or iron compounds, which become imbedded in the eye, may cause rust stains unless removed fairly promptly.
- Nickel and nickel oxides: Nickel may cause allergic skin sensitization. Nickel oxide may cause an allergic skin.
- Chromium and chromium oxides: Hexavalent chrome causes damage to gastrointestinal tract, lung, severe skin burns and eye damage, serious eye damage, skin contact may cause an allergic skin reaction. Inhalation may cause allergic or asthmatic symptoms or breathing difficulties.



Safety Data Sheet (SDS)

Revision: 06/13/2018

### Section 11 - Toxicological Information (continued)

### Acute Effects by component: (continued)

- Tungsten: Not Reported/Not Classified
- Cobalt and cobalt oxides: May cause skin, eye and allergic skin reactions.
- Molybdenum and oxides: Molybdenum causes skin and eye irritation. Molybdenum oxide is toxic if swallowed, and causes eye irritation.
- Copper and copper oxides: Copper may cause allergic skin reaction. Copper oxide is harmful if swallowed, causes skin and eye irritation, and may cause an allergic skin reaction.
- Aluminum and aluminum oxides: Inhalation may cause cough.
- Manganese and manganese oxides: Manganese and Manganese oxide are harmful if swallowed.
- Vanadium and vanadium Pentoxide: Vanadium oxide is fatal if swallowed or inhaled, and may be harmful in contact with skin.
- Silicon and oxides: May be harmful if swallowed.
- Carbon: Not Reported/Not classified

#### Delayed (chronic) Effects by component:

- Iron and iron oxides: Chronic inhalation of excessive concentrations of iron oxide fumes or dusts may result in the development of a benign pneumoconiosis, called siderosis, which is observable as an x-ray change. No physical impairment of lung function has been associated with siderosis. Inhalation of excessive concentrations of ferric oxide may enhance the risk of lung cancer development in workers exposed to pulmonary carcinogens. Iron oxide is listed as a Group 3 (not classifiable) carcinogen by the International Agency for Research on Cancer (IARC).
- Nickel and nickel oxides: Exposure to nickel dusts and fumes can cause sensitization dermatitis, respiratory irritation, asthma, pulmonary fibrosis, edema, and may cause nasal or lung cancer in humans. Nickel causes damage to lungs through prolonged or repeated inhalation exposure. IARC lists nickel and certain nickel compounds as Group 2B carcinogens (sufficient animal data). ACGIH 2017 TLVs® and BEIs® lists insoluble nickel compounds as confirmed human carcinogens. Nickel is suspected of damaging the unborn child.
- Chromium and chromium oxides: The health hazards associated with exposure to chromium are dependent upon its oxidation state. The metal form (chromium as it exists in this product) is of very low toxicity. The hexavalent form is very toxic. Repeated or prolonged exposure to hexavalent chromium compounds may cause respiratory irritation, nosebleed, ulceration and perforation of the nasal septum. Industrial exposure to certain forms of hexavalent chromium has been related to an increased incidence of cancer. NTP (The National Toxicology Program) Fourth Annual report on Carcinogens cites "certain Chromium compounds" as human carcinogens. ACGIH has reviewed the toxicity data and concluded that chromium metal is not classifiable as a human carcinogen. Hexavalent chromium may cause genetic defects and is suspected of damaging the unborn child. Developmental toxicity in the mouse, suspected of damaging fertility or the unborn child.
- Tungston: Not Reported/Not Classified
- Cobalt: Chronic exposure to cobalt metal, dust, or fume may cause respiratory or dermatologic signs and symptoms. Following skin sensitization, contact with cobalt causes eruptions of dermatitis increases and on frictional surfaces of the arms, legs, and neck. Chronic respiratory exposure results in reduced lung function, increased fibrotic changes on chest X-ray, production of scanty mucoid sputum, and shortness of breath.
- Molybdenum and oxides: Certain handling operations, such as burning and welding, may generate both insoluble molybdenum compounds (metal and molybdenum dioxide) and soluble molybdenum compounds (molybdenum trioxide). Molybdenum compounds generally exhibit a low order of toxicity with the trioxide the more toxic. However, some reports indicate that the dust of the molybdenum metal, molybdenum dioxide and molybdenum trioxide may cause eye, skin, nose and throat irritation in animals. Also, has been reported to cause induction of tumors in experimental animals, suspected of causing cancer. Molybdenum oxide is suspected of causing cancer in humans.
- Copper and copper oxides: Inhalation of high concentrations of freshly formed oxide fumes and dusts of copper can cause metal fume fever. Chronic inhalation of copper dust has caused, in animals, hemolysis of the red blood cells, deposition of hemofuscin in the liver and pancreas, injury to lung cells and gastrointestinal symptoms.
- Aluminum and aluminum oxides: Considered to be an inert or nuisance dust.
- Manganese and manganese oxides: Chronic exposure to high concentrations of manganese fumes and dusts may adversely affect the central nervous system with symptoms including languor, sleepiness, weakness, emotional disturbances, spastic gait, mask-like facial expression and paralysis. Animal studies indicate that manganese exposure may increase susceptibility to bacterial and viral infections. Occupational overexposure (Manganese) is a progressive, disabling neurological syndrome that typically begins with relatively mild symptoms and evolves to include altered gait, fine tremor, and sometimes, psychiatric disturbances. May cause damage to lungs with repeated or prolonged exposure. Neurobehavioral alterations in worker populations exposed to MnO including: speed and coordination of motor function are especially impaired.
- Vanadium and Vanadium Pentoxide: Vanadium is considered non-toxic. Excessive long term or repeated exposures to vanadium compounds, especially vanadium pentoxide, may result in chronic pulmonary changes such as emphysema or bronchitis. Vanadium pentoxide is suspected of damaging fertility or the unborn child. Vanadium pentoxide is fatal if swallowed or inhaled. It causes damage to lungs by single, repeated or prolonged exposure.
- Silicon and oxides: Silicon dusts are a low health risk by inhalation and should be treated as a nuisance dust. Eye contact with pure material can cause particulate irritation. Skin contact with silicon dusts may cause physical abrasion.
- Carbon: Chronic inhalation may lead to decreased pulmonary function.

### **Section 12 - Ecological Information**

12(a) Ecotoxicity (aquatic & terrestrial): No Data Available for Stainless Steel Scrap as sold/shipped. However, individual components of the product when processed have been found to be toxic to the environment. Metal dusts may migrate into soil and groundwater and be ingested by wildlife as follows:

- Nickel Oxide: IUCLID found LC<sub>50</sub> in fish, invertebrates and algae > 100 mg/l.
- Iron Oxide:  $LC_{50}$ : >1000 mg/L; Fish 48 h- $EC_{50}$  > 100 mg/L (Currenta, 2008k); 96 h- $LC_{0}$  ≥ 50,000 mg/L Test substance: Bayferrox 130 red (95 97% Fe<sub>2</sub>O<sub>3</sub>; < 4% SiO<sub>2</sub> and Al<sub>2</sub>O<sub>3</sub>) (Bayer, 1989a).
- 12(b) Persistence & Degradability: No Data Available for Stainless Steel Scrap as sold/shipped or individual components.



Safety Data Sheet (SDS)

Revision: 06/13/2018

### **Section 12 - Ecological Information (continued)**

12(c) Bioaccumulative Potential: No Data Available for Stainless Steel Scrap as sold/shipped or individual components.

12(d) Mobility (in soil): No data available for Stainless Steel Scrap as sold/shipped. However, individual components of the product have been found to be absorbed by plants from soil.

12(e) Other adverse effects: None Known

**Additional Information:** 

Hazard Category: Not Reported Signal Word: No Signal Word

**Hazard Symbol:** No Symbol **Hazard Statement:** No Statement

### **Section 13 - Disposal Considerations**

**Disposal:** Steel scrap should be recycled whenever possible. Product dusts and fumes from processing operations should also be recycled, or classified by a competent environmental professional and disposed of in accordance with applicable federal, state or local regulations.

**Container Cleaning and Disposal:** Follow applicable federal, state and local regulations. Observe safe handling precautions. European Waste Catalogue (EWC): 16-01-17 (ferrous metals), 12-01-99 (wastes not otherwise specified), 16-03-04 (off specification batches and unused products), or 15-01-04 (metallic packaging).

Please note this information is for Stainless Steel Scrap in its original form. Any alterations can void this information.

### **Section 14 - Transport Information**

#### 14 (a-g) Transportation Information:

**US Department of Transportation (DOT)** under 49 CFR 172.101 **does not** regulate **Stainless Steel Scrap** as a hazardous material. All federal, state, and local laws and regulations that apply to the transport of this type of material must be adhered to.

Shipping Name: Not Applicable (NA)	<b>Packaging Authorizations</b>	<b>Quantity Limitations</b>
Shipping Symbols: NA	a) Exceptions: NA	a) Passenger, Aircraft, or Railcar: NA
Hazard Class: NA	b) Group: NA	b) Cargo Aircraft Only: NA
UN No.: NA	c) Authorization: NA	Vessel Stowage Requirements
Packing Group: NA		a) Vessel Stowage: NA
DOT/ IMO Label: NA		b) Other: NA
Special Provisions (172.102): NA		DOT Reportable Quantities: NA

International Maritime Dangerous Goods (IMDG) and the Regulations Concerning the International Carriage of Dangerous Goods by Rail (RID) classification, packaging and shipping requirements follow the US DOT Hazardous Materials Regulation.

Regulations Concerning the International Carriage of Dangerous Goods by Road (ADR) does not regulate Stainless Steel Scrap as a hazardous material.

Shipping Name: Not Applicable (NA)	Packaging	Portable Tanks & Bulk Containers
Classification Code: NA	a) Packing Instructions: NA	a) Instructions: NA
UN No.: NA	b) Special Packing Provisions:	b) Special Provisions: NA
Packing Group: NA	NA	
ADR Label: NA	c) Mixed Packing Provisions: NA	
Special Provisions: NA		
Limited Quantities: NA		

International Air Transport Association (IATA) does not regulate Stainless Steel Scrap as a hazardous material.

Shipping Name: Not Applicable (NA)		Passenger & Cargo Aircraft		Cargo Aircraft Only	<b>Special Provisions:</b>
Class/Division: NA		Limited Quantity (EQ)		Pkg Inst: NA	NA
Hazard Label (s): NA		Pkg Inst: NA	Pkg Inst: NA		
UN No.: NA				Max Net Qty/Pkg:	ERG Code: NA
Packing Group: NA		Max Net Qty/Pkg:	Max Net Qty/Pkg:	NA	
Excepted Quantities (EQ): NA		NA	NA		
Pkg Inst – Packing Instructions	Max Net Qty/Pkg - Ma	aximum Net Quantity per Pac	kage	ERG – Emergency Resp	onse Drill Code

Transport Dangerous Goods (TDG) Classification: Stainless Steel Scrap does not have a TDG classification.

## **Section 15 - Regulatory Information**

**Regulatory Information**: The following listing of regulations relating to an OmniSource Corporation may not be complete and should not be solely relied upon for all regulatory compliance responsibilities. This product and/or its constituents are subject to the following regulations:

**OSHA Regulations:** Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-2, Z-3): The product, **Stainless Steel Scrap** as a mixture is not listed. However, individual components of the product are listed: Refer to Section 8, Exposure Controls and Personal Protection.



Safety Data Sheet (SDS)

Revision: 06/13/2018

### **Section 15 - Regulatory Information (continued)**

EPA Regulations: The product, Stainless Steel Scrap is not listed as a mixture. However, individual components of the product are listed:

Components	Regulations
Iron	TSCA, SDWA
Nickel	CERCLA, CWA, SARA 313, TSCA
Chromium	CERCLA, SARA 313
Cobalt	SARA 313
Molybdenum	TSCA
Copper	CERCLA, CWA, SARA 313, TSCA, SDWA
Aluminum	SARA 313, TSCA, SDWA
Manganese	SARA 313, TSCA
Vanadium	TSCA

SARA 311/312 Potential Hazard Categories: Immediate Acute Health Hazard; Delayed Chronic Health Hazard

Section 313 Supplier Notification: The product, Stainless Steel Scrap contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act and 40 CFR part 372:

CAS#	Chemical Name	Percent by Weight
7440-02-0	Nickel	36 max
7440-47-3	Chromium	27 max
7440-48-4	Cobalt	12 max
7440-50-8	Copper	5 max
7429-90-5	Aluminum	5 max
7439-96-5	Manganese	5 max

#### **Regulations Key:**

CAA Clean Air Act (42 USC Sec. 7412; 40 CFR Part 61 [As of: 8/18/06])

CERCLA Comprehensive Environmental Response, Compensation and Liability Act (42 USC Secs. 9601(14), 9603(a); 40 CFR Sec. 302.4, Table 302.4, Table 302.4 and App. A)

CWA Clean Water Act (33 USC Secs. 1311; 1314(b), (c), (e), (g); 136(b), (c); 137(b), (c) [as of 8/2/06])

RCRA Resource Conservation Recovery Act (42 USC Sec. 6921; 40 CFR Part 261 App VIII)

SARA Superfund Amendments and Reauthorization Act of 1986 Title III Section 302 Extremely Hazardous Substances (42 USC Secs. 11023, 13106; 40 CFR sec. 372.65) and Section 313 Toxic Chemicals (42 USC Secs. 11023, 13106; 40 CFR sec. 372.65 [as of 6/30/05])

TSCA Toxic Substance Control Act (15 U.S.C. s/s 2601 et seq. [1976])

SDWA Safe Drinking Water Act (42 U.S.C. s/s 300f et seq. [1974])

**State Regulations:** The product, **Stainless Steel Scrap** as a mixture is not listed in any state regulations. However, individual components of the product are listed in various state regulations:

Pennsylvania Right to Know: Contains regulated material in the following categories:

- Hazardous Substances: Nickel, Chromium, Tungsten, Cobalt, Molybdenum, Copper, Aluminum, Manganese, Vanadium, Silicon
- Environmental Hazards: Nickel, Chromium, Cobalt, Copper, Aluminum, Manganese, Vanadium
- Special Hazardous Substance: Nickel and Chromium

California Prop 65 WARNING: This product can expose you to chemicals including lead and lead compounds, which is known to the State of California to cause cancer, and lead, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

New Jersey: Contains regulated material in the following categories:

- Hazardous Substance: Nickel, Chromium, Tungsten, Cobalt, Molybdenum, Copper, Aluminum (dust and fume), Manganese, Vanadium, Silicon
- Environmental Hazard: Nickel, Chromium, Cobalt, Copper, Manganese, Vanadium
- Special Hazardous Substance: Chromium, Tungsten, Cobalt, Aluminum (dust and fume), Manganese, Silicon

Minnesota: Nickel, Chromium, Cobalt, Molybdenum, Manganese

Massachusetts: Nickel compounds, Chromium, Cobalt, Molybdenum, Copper compounds, Aluminum (dust and fume), Manganese compounds, Vanadium, Silicon

#### Other Regulations:

WHMIS Classification (Canadian): The product, Stainless Steel Scrap is not listed as a mixture. However individual components are listed.

Ingredients	WHMIS Classification
Nickel	Skin sensitization – Category 1; Carcinogenicity – Category 2; Specific target organ toxicity – repeated exposure - Category 1
Chromium	Combustible dusts
Cobalt	Respiratory sensitization - Category 1; Skin sensitization - Category 1; Carcinogenicity - Category 2
Copper	Combustible Dusts - Category 1
Manganese	Reproductive toxicity - Category 2; Specific target organ toxicity - repeated exposure - Category 1; Combustible dusts
Silicon	Flammable solids - Category 2; Combustible dusts



Safety Data Sheet (SDS)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

### **Section 16 - Other Information**

Prepared By: Steel Dynamics Inc (SDI)

Revision History: 06/13/2018 - update to comply w/ OSHA 2012 GHS & Canada WHMIS

Hazardous Material Identification System (HMIS) Classification

2015 GHS

03/21/2013 - ANSI format to OSHA GHS

 $11/04/7011-regulatory\ update$ 

1/26/2010 - regulatory update

Health Hazard Fire Hazard

### •

Expiration Date: 06/13/2021

8/07/2008 - regulatory update

10/06/2005 – regulatory update

7/19/2002 - regulatory update

7/08/1998 - Original



Physical Hazard 0

HEALTH= 1, Denotes possible chronic hazard if airborne dusts or fumes are generated

Irritation or minor reversible injury possible. FIRE= **0**, Materials that will not burn.

PHYSICAL HAZARD= 0, Materials that are normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosives.

HEALTH = 1, Exposure could cause irritation but only minor residual injury even if no treatment is given.

Revision: 06/13/2018

FLAMMABILITY = 0, Materials that will not burn.

 $\ensuremath{\mathsf{INSTABILITY}} = 0,$  Normally stable, even under fire exposure conditions, and are not reactive with water.

#### ABBREVIATIONS/ACRONYMS:

ACGIH	American Conference of Governmental Industrial Hygienists			
BEIs	Biological Exposure Indices			
CAS	Chemical Abstracts Service			
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act			
CFR	Code of Federal Regulations			
CNS	Central Nervous System			
GI, GIT	Gastro-Intestinal, Gastro-Intestinal Tract			
HMIS	Hazardous Materials Identification System			
IARC	International Agency for Research on Cancer			
LC50	Median Lethal Concentration			
LD50	Median Lethal Dose			
LD Lo	Lowest Dose to have killed animals or humans			
LEL	Lower Explosive Limit			
LOEL	Lowest Observed Effect Level			
LOAEC	Lowest Observable Adverse Effect Concentration			
$\mu g/m^3$	microgram per cubic meter of air			
mg/m³	milligram per cubic meter of air			
mppcf	million particles per cubic foot			
MSHA	Mine Safety and Health Administration			
NFPA	National Fire Protection Association			

NIF	No Information Found		
NIOSH	National Institute for Occupational Safety and Health		
NTP	National Toxicology Program		
ORC	Organization Resources Counselors		
OSHA	Occupational Safety and Health Administration		
PEL	Permissible Exposure Limit		
PNOR	Particulate Not Otherwise Regulated		
PNOC	Particulate Not Otherwise Classified		
PPE	Personal Protective Equipment		
ppm	parts per million		
RCRA	Resource Conservation and Recovery Act		
RTECS	Registry of Toxic Effects of Chemical Substances		
SARA	Superfund Amendment and Reauthorization Act		
SCBA	Self-contained Breathing Apparatus		
SDS	Safety Data Sheet		
STEL	Short-term Exposure Limit		
TLV	Threshold Limit Value		
TWA	Time-weighted Average		
UEL	Upper Explosive Limit		

**Disclaimer:** This information is taken from sources or based upon data believed to be reliable. However, OmniSource, Inc. makes no warranty as to the absolute correctness or sufficiency of any of the foregoing or that additional or other measures may not be required under particular conditions.



Omnsource	•	
The Best in Metals Recycling	Safety Data Sheet (SDS)	<b>Revision:</b> 06/13/2018