









# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.07.2020

Page 5 of 15

## Galvanized Steel Deck (Painted and Unpainted)

Repeated or prolonged inhalation of vanadium and vanadium oxide dust or fumes may cause damage to the lungs resulting in chronic bronchitis and pneumonitis. Chronic exposure may cause a greenish-black discoloration of the tongue.

Repeated or prolonged exposure to fumes and dust may cause cancer.

Inhalation of nickel and nickel oxide fume and dust may cause lung cancer.

Exposure to hexavalent chromium may cause cancer. Studies have shown that chromate production workers exposed to hexavalent chromium compounds have an excess of lung and sinus cancers.

Inhalation of excessive concentrations of iron and iron oxide dust and fume may enhance the risk of lung cancer development in workers exposed to carcinogens.

### Immediate medical attention and special treatment

#### Specific treatment:

Not determined or not applicable.

#### Notes for the doctor:

Treat symptomatically.

## SECTION 5: Firefighting measures

### Extinguishing media

#### Suitable extinguishing media:

Use extinguishers appropriate for surrounding materials.

#### Unsuitable extinguishing media:

Not determined or not applicable.

### Specific hazards during fire-fighting:

Thermal decomposition may release irritating and toxic fumes including, but not limited to, iron oxides, manganese oxides, carbon oxides, chromium oxides, nickel oxides, silicon oxides, vanadium oxides and zinc oxides.

### Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

### Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

## SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Not applicable to product as supplied, shipped and sold.

For spills involving dust generated from further processing: Wear recommended personal protective equipment (see Section 8). Avoid contact with eyes, skin and clothing. Do not breathe dust or fumes. Wear suitable respiratory protection if inhalation of airborne dust is possible. Avoid generation of dust or actions that result in dust becoming airborne. Wash thoroughly after handling.

### Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

### Methods and material for containment and cleaning up:

Collect material and place in a suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

### Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.07.2020

Page 6 of 15

### Galvanized Steel Deck (Painted and Unpainted)

#### SECTION 7: Handling and storage

**Precautions for safe handling:**

Avoid contact with sharp edges and hot surfaces. Use appropriate gloves and tools to ensure safe handling (see Section 8 for recommended personal protective equipment). Use work methods which minimize dust/fume production. Do not breathe fumes and dusts generated during further processing (such as welding, soldering, smelting, grinding, or polishing). Observe safety measures suited to the coating(s) when handling, cutting or melting. The organic material(s) of the coating(s) may generate fumes or gases when heated or melted. Follow the recommendations in ANSI Z49.1, Safety in welding and cutting (ANSI=American National Standard Institute).

**Conditions for safe storage, including any incompatibilities:**

Store in a dry place. Store away from heat, open flames and other sources of ignition. Store away from incompatible materials (See Section 10).

#### SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

**Occupational Exposure limit values:**

Country (Legal Basis)	Substance	Identifier	Permissible concentration
OSHA	Iron	7439-89-6	8-Hour TWA-PEL: 10 mg/m <sup>3</sup> (As Iron Oxide Fume or Dust)
	Manganese	7439-96-5	Ceiling Limit: 5 mg/m <sup>3</sup>
	Manganese	7439-96-5	TWA: 1 mg/m <sup>3</sup> ([Fume.] )
	Chromium	7440-47-3	8-Hour TWA-PEL: 1 mg/m <sup>3</sup> (Chromium, Metal & Insoluble Salts as Cr)
	Chromium	7440-47-3	8-Hour TWA-PEL: 0.5 mg/m <sup>3</sup> (for chromium (II) or (III) compounds)
	Chromium	7440-47-3	8-Hour TWA-PEL: 0.005 mg/m <sup>3</sup> (for chromium VI and chromium oxides)
	Chromium	7440-47-3	Level Limit Value: 0.0025 mg/m <sup>3</sup> (for chromium VI and chromium oxides - Immediate Action Level)
	Silicon	7440-21-3	8-Hour TWA-PEL: 15 mg/m <sup>3</sup> (total dust)
	Silicon	7440-21-3	8-Hour TWA-PEL: 5 mg/m <sup>3</sup> (respirable fraction)
	Nickel	7440-02-0	8-Hour TWA-PEL: 1 mg/m <sup>3</sup> (As Ni)
	Vanadium	7440-62-2	PEL Ceiling: 0.1 mg/m <sup>3</sup> (as V <sub>2</sub> O <sub>5</sub> - fume)
	Vanadium	7440-62-2	PEL Ceiling: 0.5 mg/m <sup>3</sup> (as V <sub>2</sub> O <sub>5</sub> - respirable dust)
	Carbon black	1333-86-4	8-Hour TWA-PEL: 3.5 mg/m <sup>3</sup>
	Diantimony trioxide	1309-64-4	8-Hour TWA-PEL: 0.5 mg/m <sup>3</sup> (Antimony compounds, as Sb)
	Zinc Oxide	1314-13-2	8-Hour TWA-PEL: 5 mg/m <sup>3</sup> (fume)
Zinc Oxide	1314-13-2	8-Hour TWA-PEL: 15 mg/m <sup>3</sup> (total dust)	

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.07.2020

Page 7 of 15

### Galvanized Steel Deck (Painted and Unpainted)

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Zinc Oxide	1314-13-2	8-Hour TWA-PEL: 5 mg/m <sup>3</sup> (respirable dust)
NIOSH	Iron	7439-89-6	REL: 5 mg/m <sup>3</sup> (As Iron Oxide Fume or Dust)
	Iron	7439-89-6	IDLH: 2500 mg/m <sup>3</sup> (As Iron Oxide Fume or Dust)
	Manganese	7439-96-5	REL-TWA: 1 mg/m <sup>3</sup> (up to 10 hrs.)
	Manganese	7439-96-5	15-Minute STEL: 3 mg/m <sup>3</sup>
	Manganese	7439-96-5	IDLH: 500 mg/m <sup>3</sup>
	Manganese	7439-96-5	IDLH: 500 mg/m <sup>3</sup>
	Manganese	7439-96-5	STEL: 3 mg/m <sup>3</sup>
	Manganese	7439-96-5	REL: 1 mg/m <sup>3</sup>
	Chromium	7440-47-3	REL-TWA: 0.5 mg/m <sup>3</sup> (Chromium, Metal & Insoluble Salts as Cr)
	Chromium	7440-47-3	IDLH: 250 mg/m <sup>3</sup> (Chromium, Metal & Insoluble Salts as Cr)
	Chromium	7440-47-3	REL-TWA: 0.0002 mg/m <sup>3</sup> (for chromium VI and chromium oxides)
	Silicon	7440-21-3	REL-TWA: 5 mg/m <sup>3</sup> (respirable-up to 10 hrs.)
	Silicon	7440-21-3	REL-TWA: 10 mg/m <sup>3</sup> (total dust - up to 10 hrs.)
	Nickel	7440-02-0	REL: 0.01 mg/m <sup>3</sup> (As Ni, for up to a 10-h workday during a 40 h workweek)
	Nickel	7440-02-0	IDLH: 10 mg/m <sup>3</sup>
	Vanadium	7440-62-2	15-Minute STEL: 3 mg/m <sup>3</sup>
	Vanadium	7440-62-2	Ceiling Limit: 0.05 mg/m <sup>3</sup> (as V <sub>2</sub> O <sub>5</sub> - 15 min.)
	Vanadium	7440-62-2	IDLH: 35 mg/m <sup>3</sup>
	Fibrous glass	65997-17-3	REL: 3 fibers/cm <sup>3</sup> (Fibrous glass dust & Mineral wool fiber, fibers)
	Fibrous glass	65997-17-3	REL: 5 mg/m <sup>3</sup> (Fibrous glass dust & Mineral wool fiber, Total)
	Carbon black	1333-86-4	REL-TWA: 3.5 mg/m <sup>3</sup> (10 hr)
	Carbon black	1333-86-4	IDLH: 1750 mg/m <sup>3</sup>
	Carbon black	1333-86-4	REL-TWA: 0.1 mg/m <sup>3</sup> (10hr - in presence of polycyclic aromatic hydrocarbons)
	Diantimony trioxide	1309-64-4	IDLH: 50 mg/m <sup>3</sup> (Antimony compounds, As Sb)
	Diantimony trioxide	1309-64-4	REL-TWA: 0.5 mg/m <sup>3</sup> (10-hour workday; Antimony compounds, as Sb)
	Zinc Oxide	1314-13-2	REL-TWA: 5 mg/m <sup>3</sup> (up to 10 hr.)
	Zinc Oxide	1314-13-2	Ceiling Limit: 15 mg/m <sup>3</sup>
Zinc Oxide	1314-13-2	IDLH: 500 mg/m <sup>3</sup>	

## Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.07.2020

Page 8 of 15

### Galvanized Steel Deck (Painted and Unpainted)

Country (Legal Basis)	Substance	Identifier	Permissible concentration
ACGIH	Iron	7439-89-6	8-Hour TWA: 5 mg/m <sup>3</sup> (Iron Oxide Dust (respirable particulate))
	Manganese	7439-96-5	8-Hour TWA: 0.02 mg/m <sup>3</sup> (respirable particulate matter)
	Manganese	7439-96-5	8-Hour TWA: 0.1 mg/m <sup>3</sup> (inhalable particulate matter)
	Chromium	7440-47-3	8-Hour TWA: 0.5 mg/m <sup>3</sup> (inhalable particulate matter - Chromium, Metal & Insoluble Salts as Cr)
	Chromium	7440-47-3	8-Hour TWA: 0.0002 mg/m <sup>3</sup> (for chromium VI and chromium oxides - inhalable particulate matter)
	Chromium	7440-47-3	15-Minute STEL: 0.0005 mg/m <sup>3</sup> (for chromium VI and chromium oxides - inhalable particulate matter)
	Nickel	7440-02-0	8-Hour TWA: 1.5 mg/m <sup>3</sup> (Inhalable Fraction)
	Vanadium	7440-62-2	8-Hour TWA: 0.05 mg/m <sup>3</sup> (as V <sub>2</sub> O <sub>5</sub> - inhalable particulate matter)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Continuous filament glass fibers; glass wool fibers)
	Fibrous glass	65997-17-3	8-Hour TWA: 5 mg/m <sup>3</sup> (Continuous filament glass fibers, inhalable fraction)
	Fibrous glass	65997-17-3	8-Hour TWA: 0.2 fibers/cm <sup>3</sup> (Refractory ceramic fibers)
	Carbon black	1333-86-4	8-Hour TWA: 3 mg/m <sup>3</sup> (inhalable particulate matter)
	Diantimony trioxide	1309-64-4	8-Hour TWA: 0.5 mg/m <sup>3</sup> (Antimony compounds, as Sb)
	Diantimony trioxide	1309-64-4	8-Hour TWA: 0.02 mg/m <sup>3</sup> (Antimony Trioxide, Inhalable fraction)
	Zinc Oxide	1314-13-2	8-Hour TWA: 2 mg/m <sup>3</sup> (respirable particulate matter)
	Zinc Oxide	1314-13-2	15-Minute STEL: 10 mg/m <sup>3</sup> (respirable particulate matter)
United States(California)	Manganese	7439-96-5	8-Hour TWA: 0.2 mg/m <sup>3</sup>
	Manganese	7439-96-5	15-Minute STEL: 3 mg/m <sup>3</sup>
	Manganese	7439-96-5	STEL: 3 mg/m <sup>3</sup>
	Manganese	7439-96-5	PEL: 0.2 mg/m <sup>3</sup>
	Manganese	7439-96-5	REL: 0.09 ug/m <sup>3</sup> (Chronic Inhalation)
	Silicon	7440-21-3	8-Hour TWA-PEL: 10 mg/m <sup>3</sup> (total dust)
	Silicon	7440-21-3	8-Hour TWA-PEL: 5 mg/m <sup>3</sup> (respirable fraction)



# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.07.2020

Page 9 of 15

## Galvanized Steel Deck (Painted and Unpainted)

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Glass, fibrous)
	Fibrous glass	65997-17-3	8-Hour TWA: 0.2 fibers/cm <sup>3</sup> (Refractory ceramic fiber)
	Carbon black	1333-86-4	8-Hour TWA-PEL: 3.5 mg/m <sup>3</sup>
	Diantimony trioxide	1309-64-4	8-Hour TWA-PEL: 0.5 mg/m <sup>3</sup> (Antimony compounds, as Sb)
	Zinc Oxide	1314-13-2	8-Hour TWA-PEL: 5 mg/m <sup>3</sup> (dust)
United States	Zinc Oxide	1314-13-2	15-Minute STEL: 15 mg/m <sup>3</sup> (dust)

### Biological limit values:

No biological exposure limits noted for the ingredient(s).

### Information on monitoring procedures:

Not determined or not applicable.

### Appropriate engineering controls:

The engineering controls described below are recommended only if hazardous chemicals are made available for exposure during further processing of this product.

Use local exhaust, mechanical ventilation or additional engineering measures to maintain airborne concentration below any occupational exposure limits. Ensure that Emergency eye wash station and safety shower are in good working order and in the immediate vicinity of any possible exposure.

### Personal protection equipment

#### Eye and face protection:

It is recommended that eye protection be worn at all times in a manufacturing or industrial environment. Wear safety goggles or safety glasses with side shields. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

A face shield is recommended, in addition to safety glasses or goggles, during sawing, grinding, or machining.

A welding helmet with appropriate shaded shield is required during welding, burning, or brazing.

#### Skin and body protection:

Wear protective gloves and suitable protective clothing. While handling product and/or steel packing material wear cut resistant gloves and sleeves for laceration protection.

When material is heated, wear gloves to protect against thermal burns. Thermally protective apron and long sleeves are recommended when volume of hot material is significant.

The skin protection described below is necessary only if hazardous chemicals are made available for exposure during further processing of this product.

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

#### Respiratory protection:

The respiratory protection described below is necessary only if hazardous chemicals are made available for exposure during further processing of this product.

In case of insufficient ventilation, wear suitable respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear a properly fitted, air-purifying or air-fed respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Use respirators and components tested and

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.07.2020

Page 10 of 15

## Galvanized Steel Deck (Painted and Unpainted)

approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### General hygienic measures:

Handle in accordance with good industrial hygiene and safety measures. Wash hands and face after handling chemical products. Wash hands before eating, drinking and smoking. Wash hands at the end of the workday. Appropriate techniques should be applied to remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Observe any medical surveillance requirements.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance	White/Gray (painted) / Metallic gray (unpainted) solid metal (with or without acoustical insulation and/or foam end pieces)
Odor	None
Odor threshold	Not determined or not available.
pH	Not determined or not available.
Melting point/freezing point	2750 °F (1510 °C) for steel component
Initial boiling point/range	Not determined or not available.
Flash point (closed cup)	Not determined or not available.
Evaporation rate	Not determined or not available.
Flammability (solid, gas)	Not determined or not available.
Upper flammability/explosive limit	Not determined or not available.
Lower flammability/explosive limit	Not determined or not available.
Vapor pressure	Not determined or not available.
Vapor density	Not determined or not available.
Density	Not determined or not available.
Relative density	7 - 8 (steel component)
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not determined or not available.
Auto/Self-ignition temperature	Not determined or not available.
Decomposition temperature	Not determined or not available.
Dynamic viscosity	Not determined or not available.
Kinematic viscosity	Not determined or not available.
Explosive properties	Not determined or not available.
Oxidizing properties	Not determined or not available.

### Other information

## SECTION 10: Stability and reactivity

### Reactivity:

Not reactive under recommended handling and storage conditions.

### Chemical stability:

Stable under recommended handling and storage conditions.

### Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

### Conditions to avoid:

Incompatible materials

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.07.2020

Page 11 of 15

## Galvanized Steel Deck (Painted and Unpainted)

### Incompatible materials:

Strong acids; Oxidizing agents

### Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### Acute toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Route	Result
Iron	oral	LD50 Rat: 30,000 mg/kg
Manganese	oral	LD50 Rat: 9000 mg/kg
Chromium	oral	LD50 Rat: >3400 mg/kg
	inhalation	LC50 Rat: >5,41 mg/L (4 h Aerosol)
Silicon	oral	LD50 Rat: 3160 mg/kg

### Skin corrosion/irritation

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

**Substance data:** No data available.

### Serious eye damage/irritation

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

#### Substance data:

Name	Result
Chromium	Causes serious eye irritation.

### Respiratory or skin sensitization

#### Assessment:

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Product data:

No data available.

#### Substance data:

Name	Result
Chromium	May cause an allergic skin reaction.
	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Nickel	May cause an allergic skin reaction.

### Carcinogenicity

#### Assessment:

Suspected of causing cancer.

**Product data:** No data available.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.07.2020

Page 12 of 15

## Galvanized Steel Deck (Painted and Unpainted)

### Substance data:

Name	Species	Result
Iron	Not Applicable	Inhalation of excessive concentrations of iron oxide may enhance the risk of lung cancer development in workers exposed to carcinogens.
Nickel		Suspected of causing cancer.

### International Agency for Research on Cancer (IARC):

Name	Classification
Chromium	Group 3
Nickel	Group 2B
Fibrous glass	Group 2B
Carbon black	Group 2B
Diantimony trioxide	Group 2B

### National Toxicology Program (NTP):

Name	Classification
Chromium	Known to be human carcinogens
Nickel	Reasonably anticipated to be human carcinogens
Fibrous glass	Reasonably anticipated to be human carcinogens

OSHA Carcinogens: Not applicable

### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

**Substance data:** No data available.

### Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

**Substance data:** No data available.

### Specific target organ toxicity (single exposure)

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

**Substance data:** No data available.

### Specific target organ toxicity (repeated exposure)

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

#### Substance data:

Name	Result
Iron	Chronic inhalation of excessive concentrations of iron fumes or dust may result in the development of a benign pneumoconiosis, called siderosis.
Nickel	Causes damage to organs (lungs) through prolonged or repeated exposure.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.07.2020

Page 13 of 15

## Galvanized Steel Deck (Painted and Unpainted)

### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Information on likely routes of exposure:

Not Applicable to product as supplied, shipped and sold.

If subjected to further processing, the anticipated routes of exposure are inhalation, skin contact and eye contact.

### Symptoms related to the physical, chemical and toxicological characteristics:

Refer to Section 4 of this SDS.

### Other information:

No data available.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

### Chronic (long-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

### Persistence and degradability

**Product data:** No data available.

**Substance data:** No data available.

### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

### Mobility in soil

**Product data:** No data available.

**Substance data:** No data available.

### Results of PBT and vPvB assessment

**Product data:**

**PBT assessment:** This product does not contain any substances that are assessed to be a PBT.

**vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

**Substance data:**

**PBT assessment:** This product does not contain any substances that are assessed to be a PBT.

**vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

**Other adverse effects:** No data available.

## SECTION 13: Disposal considerations

### Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory agencies. Dispose of in accordance with all applicable local, regional, state and federal regulations.

### Contaminated packages:

Not determined or not applicable.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.07.2020

Page 14 of 15

## Galvanized Steel Deck (Painted and Unpainted)

### SECTION 14: Transport information

#### United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

#### International Maritime Dangerous Goods (IMDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

#### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

### SECTION 15: Regulatory information

#### United States regulations

**Inventory listing (TSCA):** All ingredients are listed or exempt.

**Significant New Use Rule (TSCA Section 5):** None of the ingredients are listed.

**Export notification under TSCA Section 12(b):** None of the ingredients are listed.

**SARA Section 302 extremely hazardous substances:** None of the ingredients are listed.

**SARA Section 313 toxic chemicals:**

7439-96-5	Manganese	Listed
7440-47-3	Chromium	Listed
7440-02-0	Nickel	Listed
7440-62-2	Vanadium	Listed

**CERCLA:** Not applicable – any listed substances are intrinsically bound in the product.

**RCRA:**

7440-47-3	Chromium	Listed	D007
-----------	----------	--------	------

**Section 112(r) of the Clean Air Act (CAA):** None of the ingredients are listed.

# Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 10.07.2020

Page 15 of 15

## Galvanized Steel Deck (Painted and Unpainted)

### Massachusetts Right to Know:

7439-96-5	Manganese	Listed
7440-47-3	Chromium	Listed
7440-21-3	Silicon	Listed
7440-02-0	Nickel	Listed
7440-62-2	Vanadium	Listed

### New Jersey Right to Know:

7439-89-6	Iron	Listed
7439-96-5	Manganese	Listed
7440-47-3	Chromium	Listed
7440-21-3	Silicon	Listed
7440-02-0	Nickel	Listed
7440-62-2	Vanadium	Listed

### New York Right to Know:

7439-96-5	Manganese	Listed
7440-47-3	Chromium	Listed
7440-02-0	Nickel	Listed
7440-62-2	Vanadium	Listed

### Pennsylvania Right to Know:

7439-89-6	Iron	Listed
7439-96-5	Manganese	Listed
7440-47-3	Chromium	Listed
7440-21-3	Silicon	Listed
7440-02-0	Nickel	Listed
7440-62-2	Vanadium	Listed

### California Proposition 65:

**⚠️WARNING:** This product can expose you to Nickel; which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**⚠️WARNING:** This product can expose you to Chromium (hexavalent compounds); which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16: Other information

**Abbreviations and Acronyms:** None

### Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

**NFPA:** 0-0-0

**HMIS:** 0-0-0

**Initial preparation date:** 10.07.2020

**End of Safety Data Sheet**