



## Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 1 of 17

### Steel Deck (Painted and Unpainted)

#### SECTION 1: Identification

##### Product identifier

**Product name:** Steel Deck (Painted and Unpainted)

**Also applies to:** Steel Deck, Composite Deck, Versa-Dek®, Bridge-Dek® and Rhino-Dek®

**Additional information:** This product is not hazardous as supplied, shipped or sold. However, if subjected to further processing (such as welding, soldering, smelting, grinding, or polishing) hazardous substances may be released and made available for exposure. The Hazard Classification and corresponding label elements are applicable to this product in such a scenario. Consideration should also be given to the generation of hazardous oxides of the metals in this product and health hazards associated with those oxides. Additional consideration should be given to the release of hazardous components from product coatings and acoustical/insulation/foam materials incorporated into the product.

##### Recommended use of the product and restriction on use

**Relevant identified uses:** Roof deck, Sub floor deck

**Uses advised against:** Not determined or not applicable.

**Reasons why uses advised against:** Not determined or not applicable.

##### Manufacturer or supplier details

New Millennium Building Systems, LLC  
6115 Country Road 42  
Butler, IN 46721  
260-868-6000

New Millennium Building Systems, LLC  
100 Diuguids Lane  
Salem, VA 24153  
540-389-0211

New Millennium Building Systems, LLC  
1992 NW Bascom Norris Drive  
Lake City, FL  
260-868-6000

New Millennium Building Systems, LLC  
3565 US Highway 32 North  
Hope, AR 71801  
970-722-4100

New Millennium Building Systems, LLC  
4900 Hungerford Road  
Memphis, TN 38118  
901-969-3033

##### Emergency telephone number:

###### Canada

CHEMTREC

Domestic Shipments: 1-800-929-9300 (24 hours)

International Shipments: +1-703-742-5970 (24 hours)

Customer Number: CCN828604

#### SECTION 2: Hazard identification

##### GHS classification:

Skin sensitization, category 1

Respiratory sensitization, category 1

Carcinogenicity, category 2

# Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 2 of 17

## Steel Deck (Painted and Unpainted)

### Label elements

#### Hazard pictograms:



Signal word: Danger

#### Hazard statements:

H317 May cause an allergic skin reaction

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H351 Suspected of causing cancer

#### Precautionary statements:

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P261 Avoid breathing dust/fume/gas/mist/vapours/spray

P272 Contaminated work clothing should not be allowed out of the workplace

P280 Wear protective gloves/protective clothing/eye protection/face protection

P284 [In case of inadequate ventilation] wear respiratory protection

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

P321 Specific treatment (see Sections 4 - 8 of this SDS and any supplemental information on the product label).

P363 Wash contaminated clothing before reuse

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

P308+P313 IF exposed or concerned: Get medical advice/attention

P405 Store locked up

P501 Dispose of contents/container in accordance with all applicable regulations.

#### Hazards not otherwise classified:

METAL FUME FEVER: Excessive inhalation of metal fumes may cause a flu-like illness called "Metal Fume Fever". Symptoms include: headache, fever, chills, muscle aches, thirst, nausea, vomiting, chest soreness, fatigue, gastrointestinal pain and weakness. The symptoms usually start several hours after exposure; the attack may last 6 to 24 hours. Complete recovery generally occurs without intervention within 24 to 48 hours. Metal Fume Fever is more likely to occur after a period away from the job (after weekends or vacations) and usually last from 12 to 48 hours.

If this product is subjected to "hot work" (such as soldering, welding, brazing, smelting) hazardous by-products will be formed as oxides of the metal(s) in this product. Such metal oxides may pose additional health hazards.

Further processing of this product may compromise the product coating(s), resulting in the release hazardous fumes of gases. Observe safety measures suited to the coating(s) when handling, cutting or melting.

If acoustical/insulation/foam components are subjected to fabrication processes (such as sawing, cutting, etc.), fibrous glass, diantimony trioxide, carbon black and other hazardous ingredients may be released and made available for exposure. The occupational exposure limits for fibrous glass, diantimony trioxide and carbon black are provided in Section 8 of this SDS.

# Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 3 of 17

**Steel Deck (Painted and Unpainted)**

## SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 7439-89-6	Iron	>90
CAS number: 7439-96-5	Manganese	<2
CAS number: 7440-47-3	Chromium	<1
CAS number: Not Applicable	*Coating(s)	<1
CAS number: 7440-21-3	Silicon	<1
CAS number: 7440-02-0	Nickel	<0.4
CAS number: 7440-62-2	Vanadium	<0.2

### Additional Information:

\*Products may be coated (concentration < 1.0% by weight). Coating may contain chromium in the range of 1.5 - 2 mg of chromium/sq foot or 10 - 15 mg of chromium/sq foot depending on the treatment. SDS's for specific coatings are available upon request.

Products may contain acoustical insulation and/or foam. SDS's for insulation and foam are available upon request.

## SECTION 4: First-aid measures

### Description of first-aid measures

#### General notes:

Show this Safety Data Sheet to the doctor in attendance.

This product is not hazardous as supplied, shipped or sold. The first aid measures described below are applicable only if hazardous chemicals are made available for exposure during further processing of this product.

#### After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

#### After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

#### After eye contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

#### After ingestion:

Not a likely route of exposure.

# Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 4 of 17

## Steel Deck (Painted and Unpainted)

### Most important symptoms and effects, both acute and delayed

#### Acute symptoms and effects:

This product is not hazardous as supplied, shipped or sold. The acute effects/symptoms described below are applicable to exposure during further processing of this product.

Exposure to airborne dusts and fumes may cause skin and eye irritation (chemical and mechanical). Symptoms include redness, burning, tearing, itching and inflammation.

Exposure to airborne dusts or fumes may cause respiratory irritation. Symptoms include cough, breathing difficulties, inflammation of the mucous membranes lining the respiratory tract and nose and throat pain.

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Inhalation exposure may cause allergy, asthma symptoms or breathing difficulties. Symptoms may include cough, chronic phlegm, shortness of breath, wheezing and chest tightness. Symptoms may be delayed.

Excessive inhalation of metal fumes may cause a flu-like illness called "Metal Fume Fever". Symptoms include: headache, fever, chills, muscle aches, thirst, nausea, vomiting, chest soreness, fatigue, gastrointestinal pain and weakness. The symptoms usually start several hours after exposure; the attack may last 6 to 24 hours. Complete recovery generally occurs without intervention within 24 to 48 hours. Metal Fume Fever is more likely to occur after a period away from the job (after weekends or vacations) and usually last from 12 to 48 hours.

#### Delayed symptoms and effects:

This product is not hazardous as supplied, shipped or sold. The delayed effects/symptoms described below are applicable to exposure during further processing of this product.

Effects are dependent on exposure (dose, concentration, contact time).

Repeated or prolonged exposure to metal fumes and dust may cause damage to organs.

Prolonged or repeated inhalation exposure to excessive concentrations of iron and iron oxide fumes or dust may result in the development of a benign pneumoconiosis, called siderosis and reduced pulmonary function.

Chronic inhalation exposure to nickel and nickel compounds may cause lung fibrosis and pneumoconiosis.

Prolonged or repeated exposure to fumes and dust of manganese and manganese oxide may adversely affect the lungs, resulting in increased susceptibility to bronchitis and pneumonitis. Long-term exposure to manganese compounds may affect the central nervous system.

Repeated or prolonged inhalation of chromium oxide dust or fume may cause nasal ulceration and perforation of the nasal septum. Repeated or prolonged exposure to hexavalent chromium may damage the kidneys, resulting in kidney impairment.

Repeated or prolonged inhalation of vanadium and vanadium oxide dust or fumes may cause damage to the lungs resulting in chronic bronchitis and pneumonitis. Chronic exposure may cause a greenish-black discoloration of the tongue.

Repeated or prolonged exposure to fumes and dust may cause cancer.

Inhalation of nickel and nickel oxide fume and dust may cause lung cancer.

Exposure to hexavalent chromium may cause cancer. Studies have shown that chromate production workers exposed to hexavalent chromium compounds have an excess of lung and sinus cancers.

Inhalation of excessive concentrations of iron and iron oxide dust and fume may enhance the risk of lung cancer development in workers exposed to carcinogens.

### Immediate medical attention and special treatment

#### Specific treatment:

Not determined or not available.

#### Notes for the doctor:

Treat symptomatically.

# Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 5 of 17

## Steel Deck (Painted and Unpainted)

### SECTION 5: Fire-fighting measures

#### Extinguishing media

##### Suitable extinguishing media:

Use extinguishers appropriate for surrounding materials.

##### Unsuitable extinguishing media:

Not determined or not applicable.

#### Specific hazards during fire-fighting:

Thermal decomposition may release irritating and toxic fumes including, but not limited to, iron oxides, manganese oxides, carbon oxides, chromium oxides, nickel oxides, silicon oxide and vanadium oxides.

#### Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

#### Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

### SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures:

Not applicable to product as supplied, shipped and sold.

For spills involving dust generated from further processing: Wear recommended personal protective equipment (see Section 8). Avoid contact with eyes, skin and clothing. Do not breathe dust or fumes. Wear suitable respiratory protection if inhalation of airborne dust is possible. Avoid generation of dust or actions that result in dust becoming airborne. Wash thoroughly after handling.

#### Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

#### Methods and material for containment and cleaning up:

Collect material and place in a suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

#### Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

### SECTION 7: Handling and storage

#### Precautions for safe handling:

Avoid contact with sharp edges and hot surfaces. Use appropriate gloves and tools to ensure safe handling (see Section 8 for recommended personal protective equipment). Use work methods which minimize dust/fume production. Do not breathe fumes and dusts generated during further processing (such as

## Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 6 of 17

### Steel Deck (Painted and Unpainted)

welding, soldering, smelting, grinding, or polishing). Observe safety measures suited to the coating(s) when handling, cutting or melting. The organic material(s) of the coating(s) may generate fumes or gases when heated or melted. Follow the recommendations in ANSI Z49.1, Safety in welding and cutting (ANSI=American National Standard Institute).

#### Conditions for safe storage, including any incompatibilities:

Store in a dry place. Store away from heat, open flames and other sources of ignition. Store away from incompatible materials (See Section 10).

### SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

#### Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Canada	Manganese	7439-96-5	8-Hour TWA: 0.2 mg/m <sup>3</sup> (Alberta)
	Manganese	7439-96-5	8-Hour TWA: 0.2 mg/m <sup>3</sup> (British Columbia, as Mn)
	Manganese	7439-96-5	8-Hour TWA: 0.2 mg/m <sup>3</sup> (Ontario, as Mn)
	Manganese	7439-96-5	8-Hour TWA: 1 mg/m <sup>3</sup> (Quebec, Fumes, as Mn)
	Manganese	7439-96-5	15-Minute STEL: 3 mg/m <sup>3</sup> (Quebec, Fumes, as Mn)
	Manganese	7439-96-5	8-Hour TWA: 5 mg/m <sup>3</sup> (Quebec)
	Manganese	7439-96-5	8-Hour TWA: 0.2 mg/m <sup>3</sup> (Saskatchewan, as Mn)
	Manganese	7439-96-5	15-Minute STEL: 0.6 mg/m <sup>3</sup> (Saskatchewan, as Mn)
	Nickel	7440-02-0	8-Hour TWA: 1.5 mg/m <sup>3</sup> (Alberta)
	Nickel	7440-02-0	8-Hour TWA: 0.01 mg/m <sup>3</sup> (British Columbia, as Ni)
	Nickel	7440-02-0	8-Hour TWA: 1.5 mg/m <sup>3</sup> (Manitoba, as Ni)
	Nickel	7440-02-0	8-Hour TWA: 1 mg/m <sup>3</sup> (Ontario, as Ni)
	Nickel	7440-02-0	8-Hour TWA: 1 mg/m <sup>3</sup> (Quebec)
	Nickel	7440-02-0	8-Hour TWA: 1.5 mg/m <sup>3</sup> (Saskatchewan, as Ni, Inhalable Fraction)
	Nickel	7440-02-0	15-Minute STEL: 3 mg/m <sup>3</sup> (Saskatchewan, as Ni, Inhalable Fraction)
	Carbon Black	1333-86-4	8-Hour TWA: 3 mg/m <sup>3</sup>
Alberta	Manganese	7439-96-5	TWA: 0.2 mg/m <sup>3</sup>
	Chromium	7440-47-3	8-Hour TWA: 0.5 mg/m <sup>3</sup> (Metal Chromium and Cr III compounds, as Cr.)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Glass Fibres: Continuous filament)

## Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 7 of 17

**Steel Deck (Painted and Unpainted)**

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Fibrous glass	65997-17-3	8-Hour TWA: 5 mg/m <sup>3</sup> (Glass Fibres: Continuous filament, total)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Glass Fibres: Glass Wool)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Glass Fibres: Special purpose)
	Fibrous glass	65997-17-3	8-Hour TWA: 0.2 fibers/cm <sup>3</sup> (Refractory Ceramic Fibres)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Rock Wool Fibres)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Slag Wool Fibres)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Synthetic Vitreous Fibres: Glass fibres, continuous filament)
	Fibrous glass	65997-17-3	8-Hour TWA: 5 mg/m <sup>3</sup> (Synthetic Vitreous Fibres: Glass fibres, continuous filament, total particulate)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Synthetic Vitreous Fibres: Glass fibres, special purpose)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Synthetic Vitreous Fibres: Glass fibres, special purpose)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Synthetic Vitreous Fibres: Glass wool fibres)
	Fibrous glass	65997-17-3	8-Hour TWA: 0.2 fibers/cm <sup>3</sup> (Refractory ceramic fibres)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Synthetic Vitreous Fibres: Rock wool fibres)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Synthetic Vitreous Fibres: Slag wool fibres)
	Carbon Black	1333-86-4	8-Hour TWA: 3.5 mg/m <sup>3</sup>
	Diantimony trioxide	1309-64-4	8-Hour TWA: 0.5 mg/m <sup>3</sup> (Antimony compounds, as Sb)
British Columbia	Manganese	7439-96-5	TWA: 0.2 mg/m <sup>3</sup>
	Chromium	7440-47-3	8-Hour TWA: 0.5 mg/m <sup>3</sup> (Metal Chromium (Total))
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (SYNTHETIC VITREOUS FIBRES-CONTINUOUS FILAMENT GLASS FIBERS)
	Fibrous glass	65997-17-3	8-Hour TWA: 5 mg/m <sup>3</sup> (SYNTHETIC VITREOUS FIBRES - CONTINUOUS FILAMENT GLASS FIBERS, INHALABLE)

## Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 8 of 17

**Steel Deck (Painted and Unpainted)**

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (SYNTHETIC VITREOUS FIBRES- GLASS WOOL FIBERS)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (SYNTHETIC VITREOUS FIBRES- ROCK WOOL FIBERS)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (SYNTHETIC VITREOUS FIBRES- SLAG WOOL FIBERS)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (SYNTHETIC VITREOUS FIBRES- SPECIAL PURPOSE GLASS FIBERS)
	Fibrous glass	65997-17-3	8-Hour TWA: 0.2 fibers/cm <sup>3</sup> (SYNTHETIC VITREOUS FIBRES- REFRACTORY CERAMIC FIBERS)
	Diantimony trioxide	1309-64-4	8-Hour TWA: 0.5 mg/m <sup>3</sup> (Antimony compounds, as Sb)
Ontario	Manganese	7439-96-5	TWA: 0.2 mg/m <sup>3</sup>
	Chromium	7440-47-3	8-Hour TWA: 0.5 mg/m <sup>3</sup> (Metal Chromium and Inorganic Cr III compounds, as Cr.)
	Silicon	7440-21-3	8-Hour TWA: 10 mg/m <sup>3</sup>
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cc (CONTINUOUS FILAMENT GLASS FIBERS)
	Fibrous glass	65997-17-3	8-Hour TWA: 5 mg/m <sup>3</sup> (CONTINUOUS FILAMENT GLASS FIBERS, INHALABLE FRACTION)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cc (GLASS WOOL FIBERS)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cc (ROCK WOOL FIBERS)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cc (SLAG WOOL FIBERS)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cc (SPECIAL PURPOSE GLASS FIBERS)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cc (SYNTHETIC VITREOUS FIBRES [MAN-MADE MINERAL FIBRES]: SPECIAL PURPOSE GLASS FIBRES, RESPIRABLE FIBRES)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cc (SYNTHETIC VITREOUS FIBRES [MAN-MADE MINERAL FIBRES]: SYNTHETIC VITREOUS FIBRES, NOT OTHERWISE CLASSIFIED (EXCLUDING FIBROUS GLASS DUST AND MINERAL WOOL FIBRE), RESPIRABLE FIBRES)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cc (SYNTHETIC VITREOUS FIBRES [MAN-MADE MINERAL FIBRES]: CONTINUOUS FILAMENT GLASS FIBRE, RESPIRABLE FIBRES)



## Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 9 of 17

**Steel Deck (Painted and Unpainted)**

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Fibrous glass	65997-17-3	8-Hour TWA: 5 mg/m <sup>3</sup> (SYNTHETIC VITREOUS FIBRES [MAN-MADE MINERAL FIBRES]: CONTINUOUS FILAMENT GLASS FIBRES, INHALABLE FRACTION)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cc (SYNTHETIC VITREOUS FIBRES [MAN-MADE MINERAL FIBRES]: GLASS WOOL FIBRES, RESPIRABLE FIBRES)
	Fibrous glass	65997-17-3	8-Hour TWA: 0.5 fibers/cc (SYNTHETIC VITREOUS FIBRES [MAN-MADE MINERAL FIBRES]: REFRACTORY CERAMIC FIBRES, RESPIRABLE FIBRES)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cc (SYNTHETIC VITREOUS FIBRES [MAN-MADE MINERAL FIBRES]: ROCK WOOL FIBRES, RESPIRABLE FIBRES)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cc (SYNTHETIC VITREOUS FIBRES [MAN-MADE MINERAL FIBRES]: SLAG WOOL FIBRES, RESPIRABLE FIBRES)
	Fibrous glass	65997-17-3	8-Hour TWA: 0.2 fibers/cc (REFRACTORY CERAMIC FIBRES)
	Carbon Black	1333-86-4	8-Hour TWA: 3 mg/m <sup>3</sup> (inhalable fraction)
	Diantimony trioxide	1309-64-4	8-Hour TWA: 0.5 mg/m <sup>3</sup> (Antimony compounds, as Sb)
Quebec	Manganese	7439-96-5	TWA: 0.2 mg/m <sup>3</sup>
	Chromium	7440-47-3	8-Hour TWA: 0.5 mg/m <sup>3</sup>
	Silicon	7440-21-3	8-Hour TWA: 10 mg/m <sup>3</sup> (total dust)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (FIBRES-ARTIFICIAL VITREOUS MINERAL FIBRES, INSULATION WOOL FIBRES, GLASS WOOL)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (FIBRES-ARTIFICIAL VITREOUS MINERAL FIBRES, INSULATION WOOL FIBRES, ROCK WOOL)
	Fibrous glass	65997-17-3	8-Hour TWA: 2 fibers/cm <sup>3</sup> (FIBRES-ARTIFICIAL VITREOUS MINERAL FIBRES, INSULATION WOOL FIBRES, SLANG WOOL)
	Fibrous glass	65997-17-3	8-Hour TWA: 10 mg/m <sup>3</sup> (FIBRES-ARTIFICIAL VITREOUS MINERAL FIBRES, FIBROUS GLASS, CONTINUOUS FILAMENT, TOTAL DUST)

## Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 10 of 17

**Steel Deck (Painted and Unpainted)**

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (FIBRES-ARTIFICIAL VITREOUS MINERAL FIBRES, REFRACTORY FIBRES [CERAMIC OR OTHERS])
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (FIBRES-ARTIFICIAL VITREOUS MINERAL FIBRES, FIBROUS GLASS, MICROFIBRES)
	Carbon Black	1333-86-4	8-Hour TWA: 3.5 mg/m <sup>3</sup>
	Diantimony trioxide	1309-64-4	8-Hour TWA: 0.5 mg/m <sup>3</sup> (Antimony compounds, as Sb)
Saskatchewan	Manganese	7439-96-5	15-Minute Contamination Limit: 0.6 mg/m <sup>3</sup>
	Manganese	7439-96-5	8-Hour Contamination Limit: 0.2 mg/m <sup>3</sup>
	Chromium	7440-47-3	8-Hour TWA: 0.5 mg/m <sup>3</sup> (Metal Chromium and Cr III compounds.)
	Chromium	7440-47-3	15-Minute STEL: 15 mg/m <sup>3</sup> (Metal Chromium and Cr III compounds.)
	Silicon	7440-21-3	15-Minute Contamination Limit: 20 mg/m <sup>3</sup>
	Silicon	7440-21-3	8-Hour Contamination Limit: 10 mg/m <sup>3</sup>
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Synthetic Vitreous Fibres - Continuous filament glass fibres, [respirable fibres])
	Fibrous glass	65997-17-3	8-Hour TWA: 5 mg/m <sup>3</sup> (Synthetic Vitreous Fibres - Continuous filament glass fibres, [inhalable fraction])
	Fibrous glass	65997-17-3	15-Minute STEL: 10 mg/m <sup>3</sup> (Synthetic Vitreous Fibres - Continuous filament glass fibres, [inhalable fraction])
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Synthetic Vitreous Fibres - Glass wool fibres, [respirable fibres])
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Synthetic Vitreous Fibres - Rock wool fibres, [respirable fibres])
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Synthetic Vitreous Fibres - Slag wool fibres, [respirable fibres])
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (Synthetic Vitreous Fibres - Special purpose glass fibres, [respirable fibres])
	Fibrous glass	65997-17-3	8-Hour TWA: 0.2 fibers/cm <sup>3</sup> (Synthetic Vitreous Fibres - Refractory ceramic fibres, [respirable fibres])
	Carbon Black	1333-86-4	8-Hour TWA: 3.5 mg/m <sup>3</sup>

# Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 11 of 17

## Steel Deck (Painted and Unpainted)

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Carbon Black	1333-86-4	15-Minute STEL: 7 mg/m <sup>3</sup>
	Diantimony trioxide	1309-64-4	8-Hour Contamination Limit: 0.5 mg/m <sup>3</sup> (Antimony compounds, as Sb)
	Diantimony trioxide	1309-64-4	15-Minute Contamination Limit: 1.5 mg/m <sup>3</sup>
Manitoba	Chromium	7440-47-3	8-Hour TWA: 0.5 mg/m <sup>3</sup> (Inhalable Fraction)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (CONTINUOUS FILAMENT GLASS FIBERS)
	Fibrous glass	65997-17-3	8-Hour TWA: 5 mg/m <sup>3</sup> (CONTINUOUS FILAMENT GLASS FIBERS, INHALABLE FRACTION)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (GLASS WOOL FIBERS)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (ROCK WOOL FIBERS)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (SLAG WOOL FIBERS)
	Fibrous glass	65997-17-3	8-Hour TWA: 1 fibers/cm <sup>3</sup> (SPECIAL PURPOSE GLASS FIBERS)
	Fibrous glass	65997-17-3	8-Hour TWA: 0.2 fibers/cm <sup>3</sup> (REFRACTORY CERAMIC FIBERS)
	Carbon Black	1333-86-4	8-Hour TWA: 3 mg/m <sup>3</sup>
	Diantimony trioxide	1309-64-4	8-Hour TWA: 0.5 mg/m <sup>3</sup> (Antimony compounds, as Sb)

### Biological limit values:

No biological exposure limits noted for the ingredient(s).

### Information on monitoring procedures:

Not determined or not applicable.

### Appropriate engineering controls:

The engineering controls described below are recommended only if hazardous chemicals are made available for exposure during further processing of this product.

Use local exhaust, mechanical ventilation or additional engineering measures to maintain airborne concentration below any occupational exposure limits. Ensure that Emergency eye wash station and safety shower are in good working order and in the immediate vicinity of any possible exposure.

### Personal protection equipment

#### Eye and face protection:

It is recommended that eye protection be worn at all times in a manufacturing or industrial environment. Wear safety goggles or safety glasses with side shields. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

A face shield is recommended, in addition to safety glasses or goggles, during sawing, grinding, or machining.

A welding helmet with appropriate shaded shield is required during welding, burning, or brazing.

#### Skin and body protection:

Wear protective gloves and suitable protective clothing. While handling product and/or steel packing

# Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 12 of 17

## Steel Deck (Painted and Unpainted)

material wear cut resistant gloves and sleeves for laceration protection.

When material is heated, wear gloves to protect against thermal burns. Thermally protective apron and long sleeves are recommended when volume of hot material is significant.

The skin protection described below is necessary only if hazardous chemicals are made available for exposure during further processing of this product.

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

### Respiratory protection:

The respiratory protection described below is necessary only if hazardous chemicals are made available for exposure during further processing of this product.

In case of insufficient ventilation, wear suitable respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear a properly fitted, air-purifying or air-fed respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

### General hygienic measures:

Handle in accordance with good industrial hygiene and safety measures. Wash hands and face after handling chemical products. Wash hands before eating, drinking and smoking. Wash hands at the end of the workday. Appropriate techniques should be applied to remove contaminated clothing and shoes. Wash contaminated clothing before reuse. Observe any medical surveillance requirements.

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance (physical state, color):	White/Gray (painted) or Metallic gray (unpainted) solid metal (with or without accoustical insulation and/or foam end pieces)
Odor:	None
Odor threshold:	Not determined or not available.
pH-value:	Not determined or not available.
Melting/Freezing point:	2750 °F (1510 °C) for steel component
Boiling point/range:	Not determined or not available.
Flash point:	Not determined or not available.
Evaporation rate:	Not determined or not available.
Flammability (solid, gaseous):	Not determined or not available.
Explosion limit upper:	Not determined or not available.
Explosion limit lower:	Not determined or not available.
Vapor pressure:	Not determined or not available.
Vapor density:	Not determined or not available.
Density:	Not determined or not available.
Relative density:	7 - 8 (steel component)
Solubilities:	Not determined or not available.
Partition coefficient (n-octanol/water):	Not determined or not available.

# Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 13 of 17

## Steel Deck (Painted and Unpainted)

<b>Auto/Self-ignition temperature:</b>	Not determined or not available.
<b>Decomposition temperature:</b>	Not determined or not available.
<b>Dynamic viscosity:</b>	Not determined or not available.
<b>Kinematic viscosity:</b>	Not determined or not available.
<b>Explosive properties</b>	Not determined or not available.
<b>Oxidizing properties</b>	Not determined or not available.

### Other information

## SECTION 10: Stability and reactivity

#### Reactivity:

Not reactive under recommended handling and storage conditions.

#### Chemical stability:

Stable under recommended handling and storage conditions.

#### Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

#### Conditions to avoid:

Incompatible materials

#### Incompatible materials:

Strong acids; Oxidizing agents

#### Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### Acute toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

#### Substance data:

Name	Route	Result
Iron	oral	LD50 Rat: 30,000 mg/kg
Manganese	oral	LD50 Rat: 9000 mg/kg
Chromium	oral	LD50 Rat: >3400 mg/kg
	inhalation	LC50 Rat: >5.41 mg/L (4 h Aerosol)
Silicon	oral	LD50 Rat: 3160 mg/kg

### Skin corrosion/irritation

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

**Substance data:** No data available.

### Serious eye damage/irritation

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

# Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 14 of 17

## Steel Deck (Painted and Unpainted)

### Substance data:

Name	Result
Chromium	Causes serious eye irritation.

### Respiratory or skin sensitization

#### Assessment:

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### Product data:

No data available.

#### Substance data:

Name	Result
Chromium	May cause an allergic skin reaction.
	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Nickel	May cause an allergic skin reaction.

### Carcinogenicity

#### Assessment:

Suspected of causing cancer.

**Product data:** No data available.

#### Substance data:

Name	Species	Result
Nickel		Suspected of causing cancer.

### International Agency for Research on Cancer (IARC):

Name	Classification
Chromium	Group 3
Nickel	Group 2B

### National Toxicology Program (NTP):

Name	Classification
Chromium	Known to be human carcinogens
Nickel	Reasonably anticipated to be human carcinogens

### Germ cell mutagenicity

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

**Substance data:** No data available.

### Reproductive toxicity

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

**Substance data:** No data available.

### Specific target organ toxicity (single exposure)

**Assessment:** Based on available data, the classification criteria are not met.

#### Product data:

No data available.

**Substance data:** No data available.

# Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 15 of 17

## Steel Deck (Painted and Unpainted)

### Specific target organ toxicity (repeated exposure)

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:**

Name	Result
Nickel	Causes damage to organs through prolonged or repeated exposure.

### Aspiration toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:**

No data available.

**Substance data:** No data available.

### Information on likely routes of exposure:

Not Applicable to product as supplied, shipped and sold.

If subjected to further processing, the anticipated routes of exposure are inhalation, skin contact and eye contact.

### Symptoms related to the physical, chemical and toxicological characteristics:

Refer to Section 4 of this SDS.

### Other information:

No data available.

## SECTION 12: Ecological information

### Acute (short-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

### Chronic (long-term) toxicity

**Assessment:** Based on available data, the classification criteria are not met.

**Product data:** No data available.

**Substance data:** No data available.

### Persistence and degradability

**Product data:** No data available.

**Substance data:** No data available.

### Bioaccumulative potential

**Product data:** No data available.

**Substance data:** No data available.

### Mobility in soil

**Product data:** No data available.

**Substance data:** No data available.

### Results of PBT and vPvB assessment

**Product data:**

**PBT assessment:** This product does not contain any substances that are assessed to be a PBT.

**vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

# Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 16 of 17

## Steel Deck (Painted and Unpainted)

### Substance data:

**PBT assessment:** This product does not contain any substances that are assessed to be a PBT.

**vPvB assessment:** This product does not contain any substances that are assessed to be a vPvB.

**Other adverse effects:** No data available.

## SECTION 13: Disposal considerations

### Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory agencies. Dispose of in accordance with all applicable local, regional, state and federal regulations.

### Contaminated packages:

Not determined or not applicable.

## SECTION 14: Transport information

### Canadian Transportation of Dangerous Goods (TDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

### International Maritime Dangerous Goods (IMDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None



# Safety Data Sheet

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 10.14.2020

Page 17 of 17

## Steel Deck (Painted and Unpainted)

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Bulk Name	None
Ship type	None
Pollution category	None

## SECTION 15: Regulatory information

### Canada regulations

**Domestic substances list (DSL):** All ingredients are listed or exempt.

**Non-domestic substances list (NDSL):** None of the ingredients are listed.

## SECTION 16: Other information

**Abbreviations and Acronyms:** None

### Disclaimer:

This product has been classified in accordance with the Canadian Hazardous Products Regulations and WHMIS 2015. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial preparation date: 10.14.2020

**End of Safety Data Sheet**